


Central  
Semiconductor Corp.

**Central  
Semiconductor Corp.**  
**Central™  
Semiconductor Corp.**

145 Adams Avenue  
Hauppauge, New York 11788



2N4918  
2N4919  
2N4920

PNP Silicon Transistor  
General Purpose Power

JEDEC TO-126 Case

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N4918, 2N4919, and 2N4920 are Silicon PNP Epitaxial Base Power Transistors designed for Medium power amplifier and switching applications.

MAXIMUM RATINGS ( $T_A=25^{\circ}\text{C}$  Unless otherwise noted)

		<u>2N4918</u>	<u>2N4919</u>	<u>2N4920</u>
Collector-Base Voltage	$V_{CB0}$	40V	60V	80V
Collector-Emitter Voltage	$V_{CE0}$	40V	60V	80V
Emitter-Base Voltage	$V_{EB0}$		5.0V	
Collector Current, Continuous	$I_C$		1.0A	
Collector Current, Peak	$I_{CM}$		3.0A	
Base Current	$I_B$		1.0A	
Power Dissipation ( $T_C=25^{\circ}\text{C}$ )	$P_D$		30W	
Operating & Storage Junction Temperature	$T_J, T_{stg}$		-65 to +150°C	
Thermal Resistance, Junction to Case	$\theta_{J-C}$		3.12°C/W	

ELECTRICAL CHARACTERISTICS ( $T_C=25^{\circ}\text{C}$ )

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>MIN</u>	<u>MAX</u>	<u>UNIT</u>
$I_{CB0}$	$V_{CB}=\text{Rated } V_{CB}$		100	$\mu\text{A}$
$I_{CEV}$	$V_{CE}=\text{Rated } V_{CE0}, V_{EB}=1.5\text{V}$		100	$\mu\text{A}$
$I_{CE0}$	$V_{CE}=0.5\text{X Rated } V_{CE0}$		500	$\mu\text{A}$
$I_{EB0}$	$V_{EB}=5.0\text{V}$		1.0	mA
$BV_{CE0}$	$I_C=0.1\text{A}$	40(2N4918)		V
		60(2N4919)		V
		80(2N4920)		V
$V_{CE(s)}$	$I_C=1.0\text{A}, I_B=0.1\text{A}$		0.6	V
$V_{BE(s)}$	$I_C=1.0\text{A}, I_B=0.1\text{A}$		1.3	V
$V_{BE(on)}$	$V_{CE}=1.0\text{V}, I_C=1.0\text{A}$		1.3	V
hFE	$V_{CE}=1.0\text{V}, I_C=50\text{mA}$	40		-
hFE	$V_{CE}=1.0\text{V}, I_C=500\text{mA}$	20	100	-
hFE	$V_{CE}=1.0\text{V}, I_C=1.0\text{A}$	10		-
fT	$V_{CE}=10\text{V}, I_C=250\text{mA}, f=1.0\text{MHz}$	3.0		MHz
$C_{ob}$	$V_{CB}=10\text{V}, f=100\text{kHz}$		100	pF

