



A Schlumberger Company

**BAV17/BAV18/BAV19
BAV20/BAV21** 7.03-09
General Purpose Diodes

- $V_F \dots 1.0 \text{ V (Max) @ } 100 \text{ mA}$
- $I_R \dots 100 \text{ nA @ WIV}$

PACKAGES

BAV17	DO-35
BAV18	DO-35
BAV19	DO-35
BAV20	DO-35
BAV21	DO-35

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

Storage Temperature Range	-65°C to +200°C
Maximum Junction Operating Temperature	+175°C
Lead Temperature	+260°C

Power Dissipation (Note 2)

Maximum Total Power Dissipation at 25°C Ambient	500 mW
Linear Power Derating Factor (from 25°C)	3.33 mW/°C

Maximum Voltage and Currents

WIV	Working Inverse Voltage		
		BAV 17	20 V
		BAV 18	50 V
		BAV 19	100 V
		BAV 20	150 V
		BAV 21	200 V

I_O	Average Rectified Current	100 mA
I_F	Continuous Forward Current	300 mA
I_F	Peak Repetitive Forward Current	400 mA
$i_F(\text{surge})$	Peak Forward Surge Current	
	Pulse Width=1 μ sec.	4 A
	Pulse Width=1 sec.	1 A

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	TEST CONDITIONS
V_F	Forward Voltage			1.00 1.25	V	$I_F=100 \text{ mA}$ $I_F=200 \text{ mA}$
I_R	Reverse Current			100 15 100 15 100 15 100 15 100 15	nA μ A nA μ A nA μ A nA μ A nA μ A	$V_R=200 \text{ V}$ $V_R=200 \text{ V}, T_A=100^\circ\text{C}$ $V_R=150 \text{ V}$ $V_R=150 \text{ V}, T_A=100^\circ\text{C}$ $V_R=100 \text{ V}$ $V_R=100 \text{ V}, T_A=100^\circ\text{C}$ $V_R=50 \text{ V}$ $V_R=50 \text{ V}, T_A=100^\circ\text{C}$ $V_R=20 \text{ V}$ $V_R=20 \text{ V}, T_A=100^\circ\text{C}$
BV	Breakdown Voltage	250 200 120 80 25			V	$I_R=100 \mu\text{A}$ $I_R=100 \mu\text{A}$ $I_R=100 \mu\text{A}$ $I_R=100 \mu\text{A}$ $I_R=100 \mu\text{A}$
C	Capacitance		1.5	5.0	pF	$V_R=0, f=1 \text{ MHz}$
t_{rr}	Reverse Recovery Time (Note 3)			50	ns	$I_F=30\text{mA}, I_R=30\text{mA}, R_L=100\Omega$
diff	Differential Resistance		5.0		Ω	$I_F=10\text{mA}$

NOTES:

1. These ratings are limiting values above which the serviceability of the diode may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty-cycle operation.
3. Recovery to $I_F=3 \text{ mA}$.
4. For product family characteristic curves, refer to Chapter 4 BAV 17/18 D4, BAV 19/20/21 D1.