



F 139 B
(CB 76)



TO 18
(CB 6)



TO 39
(CB 7)



TO 92
(CB 97)

Silicon PNP transistors, general purpose (continued)
Transistors PNP silicium, usage général (suite)

T_{amb} = 25 °C

Type	Case Boîtier	P _{tot} (mW)	V _{CEO} (V) V _{CER} * V _{CEx} □	h _{21E} h _{21E} * min	h _{21E} h _{21E} * max	I _C (mA)	V _{CEsat} (V) max	I _C /I _B (mA)	f _T (MHz) min	t _s (ns) t _{off} * max	TSI 76 Page
BC 213	F 139 B○	300	-30	80	400	-2	-0,6	100/5	200		347
BC 214	F 139 B○	300	-30	140	400	-2	-0,6	100/5	200		347
BC 215	TO 72	400	-30	40	300	-150			150		353
BC 307 VI	F 139 B○	300	-45	75	150*	-2	-0,95	100/5	200 §		367
BC 307 A	F 139 B○	300	-45	125	260*	-2	-0,95	100/5	200 §		367
BC 308 VI	F 139 B○	300	-25	75*	150*	-2	-0,95	100/5	200 §		367
BC 308 A	F 139 B○	300	-25	125*	260*	-2	-0,95	100/5	200 §		367
BC 308 B	F 139 B○	300	-25	240*	500*	-2	-0,95	100/5	200 §		367
BC 309 A	F 139 B○	300	-20	125*	260*	-2	-0,95	100/5	200 §		367
BC 309 B	F 139 B○	300	-20	240*	500*	-2	-0,95	100/5	200 §		367
*BC 313	TO 39	800	-40	40	250	-150	-1	1000/100	300 §		373
BC 313 A	TO 39	800	-60	40	250	-150	-1	1000/100	300 §		373
*BC 327 cl 16	F 139 B○	625	-45	100	250	-100	-0,7	500/50	200		379
BC 328 cl 25	F 139 B○	625	-25	160	400	-100	-0,7	500/50	200		379
*BC 415	F 139 B○	240	-30	200	800	-2	-0,25	10/0,5	250 §		395
BC 416	F 139 B○	240	-45	200	800	-2	-0,25	10/0,5	250 §		395
BC 556	TO 92○	500	-65	75	250	-2	-0,65	100/5	150 §		409
BC 556 A	TO 92○	500	-65	125	250	-2	-0,65	100/5	150 §		409
*BC 557	TO 92○	500	-45	75	250	-2	-0,65	100/5	150 §		409
*BC 557 A	TO 92○	500	-45	125	250	-2	-0,65	100/5	150 §		409
*BC 558 A	TO 92○	500	-30	125	250	-2	-0,65	100/5	150 §		409
*BC 558 B	TO 92○	500	-30	220	475	-2	-0,65	100/5	150 §		409
*BC 559 A	TO 92○	500	-30	125	250	-2	-0,65	100/5	150 §		409
*BC 559 B	TO 92○	500	-30	220	475	-2	-0,65	100/5	150 §		409
BC 560 A	TO 92○	500	-45	125	250	-2	-0,65	100/5	150 §		409
BC 560 B	TO 92○	500	-45	220	485	-2	-0,65	100/5	150 §		409
BC 636	F 139 B○	1000	-45	40	250	-150	-0,5	500/50	50 §		423
BC 638	F 139 B○	1000	-60	40	160	-150	-0,5	500/50	50 §		423
BC 640	F 139 B○	1000	-80	40	160	-150	-0,5	500/50	50 §		423
BCW 92 A	F 139 B○	610	-40	100	200	-150	-0,25	150/15	135		433
BCW 92 B	F 139 B○	610	-40	150	300	-150	-0,25	150/15	135		433
BCW 93 A	F 139 B○	610	-60	100	200	-150	-0,25	150/15	135		433
BCW 93 B	F 139 B○	610	-60	150	300	-150	-0,25	150/15	135		433
BCW 96 A	F 139 B○	540	-40	100	200	-50	-0,25	50/5	135		445
BCW 96 B	F 139 B○	540	-40	150	300	-50	-0,25	50/5	135		445

* Preferred device § Typical value ○ Plastic case
Dispositif recommandé Valeur typique Boîtier plastique